

HOT MIX ASPHALT

Not classified as dangerous for supply/use.

HAZARDS

Refer to SDS for additional information on safe handling / use.
Keep out of reach of children. For industrial use only

Not classified as dangerous for supply/use. Contact with hot ASPHALT PAVING MATERIALS causes skin burns. May cause eye irritation. Fumes may cause upper respiratory irritation (nose & throat). Skin contact may increase susceptibility to sunburn.

Poisonous hydrogen sulfide gas can accumulate in the head-space of containers of certain asphalt products. Mechanical disruption (e.g., milling, cutting, chipping) of cured asphalt pavement may release crystalline silica dust from the aggregate.

Avoid breathing dust/fume/mist/vapors. As necessary, wear protective gloves/protective clothing/eye protection/face protection. Wash hands and exposed skin after use.

Company

Identification:

Supplier



101 Riverview Drive
Richland, Mississippi, Inc.

Telephone (601)376-4000

In case of fire: Extinguish with carbon dioxide, dry chemical, foam or water spray.

Description of first aid measures:

- Inhalation** Not normally required. Move person to fresh air. Apply artificial respiration if necessary. If symptoms persist, obtain medical attention.
- Skin Contact** Causes burns. Immediately cool skin where asphalt binder has adhered to skin. Allow asphalt binder which remains on the skin to fall off naturally. DO NOT REMOVE. If problem persists or coverage is extensive, get medical attention
- Eye Contact** Flush eyes with water for at least 15 minutes while holding eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation develops and persists, get medical attention
- Ingestion** Not normally required. Do not induce vomiting. Do not give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

Methods and material for containment and cleaning up: Avoid contact with skin and eyes. Allow product to cool/solidify and pick up as a solid.